FREEDOM® RXV®



Make the Most Out Of Your Joyride.

Make the most out of every ride in the new E-Z-G0° Freedom RXV with a sleek design and modern dash for maximum convenience. Further your adventure with the premier performance and efficiency of the maintenance-free ELiTE Lithium powertrain powered by Samsung SDI technology and customize your Freedom RXV with an infotainment system for maximum connectivity. Where will the Freedom RXV take you next?

ELITE LITHIUM POWERTRAIN OR EX1 GAS ENGINE WITH CLOSED LOOP EFI

PREMIUM INTERIOR

AUTOMOTIVE STYLE HANGING PEDALS



FREEDOM' RXV'



Key Features

- New Body Style
- Automotive Style Pedals
- Convex Mirror
- LED Headlights, Taillights & Brake Lights
- 18" Turf Tires
- Horn
- Integrated Storage Basket
- Energy Transfer Bumpers
- Functional Dash with Large Cupholders
- Comfortable Contoured Seats
- Oversized Bagwell
- USB Port
- Optional Rear-Facing Seat Available in 4-Passenger Models
- Optional Alloy Wheels
- Optional Premium Seats
- Automatic Parking Brake with Advanced IntelliBrake™ Technology (ELITE Only)
- State of Charge Meter (ELiTE Only)
- DC/DC Converter (ELiTE Only)
- Fuel Gauge (EX1 Only)

Optional Equipment

- Infotainment with Apple CarPlay[®] and Android Auto[™] Capabilities
- Turn Signals (Dash or Stalk Mounted)
- Accent Headlight with Premium Turn Signals

Color Options







FLITE

EX1

		=/(1	
DIMENSIONS			
OVERALL LENGTH	94.5 in (240 cm)		
OVERALL WIDTH	47.0 in (119 cm)		
OVERALL HEIGHT (W/O ROOF)	46.5 in (118 cm)	47.5 in (121 cm)	
OVERALL HEIGHT (W/ ROOF)	69.5 in (177 cm)	70.0 in (178 cm)	
WHEEL BASE	66 in (168 cm)	65.7 in (167 cm)	
FRONT WHEEL TRACK	35.5 in (90 cm)	35.5 in (90 cm)	
REAR WHEEL TRACK	38.0 in (97 cm)	38.0 in (97 cm)	
GROUND CLEARANCE @ DIFFERENTIAL	4.5 in (11 cm)	4.0 in (10 cm)	

\neg	$\overline{}$	١	٨	1	

TOWER			
POWER SOURCE	56.7 V 4-Cycle, 9.15 cu in (150 cc)		
HORSEPOWER (KW)	4.4 hp (3.3 kW) Continuous	11.5 hp (8.6 kW) J1995 Standard	
ELECTRICAL SYSTEM	56-Volt AC	Brushless DC Interal Starter Generator	
BATTERIES (TYPE)	ELiTE 2.2, 56.7V Lithium	One, 12-Volt Maintenance-Free	
KEY OR PEDAL START	Pedal		
BATTERY CHARGER	ELiTE Light World Charger 120/230 VAC, 10' DC Cord	N/A	
SPEED CONTROLLER	235-amp Solid-State AC Controller	N/A	
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)	
TRANSAXLE	Limited Slip Differential	Differential with Helical Gears	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	Forward-Reverse	
REAR AXLE RATIO	16.99:1	11:47:1 (Forward) 14:35:1 (Reverse)	

PERFORMANCE

. 2.1. 0.1. 1. 1.02		
2 or 4 Passenger		
599 lb (272 kg) (Without Batteries)	676 lb (307 kg)	
646 lb (293 kg) (With 2.2 pack)	692 lb (314 kg)	
500 lb (227 kg) (2 Passenger) or 800 lb (360kg) (4 Passenger)		
19.2 ft (5.8 m)	19.0 ft (5.8 m)	
19 mph ± 0.5 mph (31 kph ± 0.8 kph)		
	599 lb (272 kg) (Without Batteries) 646 lb (293 kg) (With 2.2 pack) 500 lb (227 kg) (2 Passenger) of 19.2 ft (5.8 m)	

STEERING & SUSPENSION

STEERING	Double-Ended Rack and Pinion	
SUSPENSION	Front: Independent A-Arm Coil-Over Shock; Rear: Mono-Leaf Spring With Hydraulic Shocks	
SERVICE BRAKE	Induction Motor	Rear Wheel Mechanical Self-Adjusting Drums
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single Point Engagement
TIRES	18 x 8.50-8 (4-ply rated)	

BODY & CHASSIS

B0B1 & 0111 (0010	
FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
AVAILABLE BODY COLORS	Almond, Black, Bright White, Burgundy, Forest Green, Inferno Red, Ivory, Metallic Charcoal, Ocean Grey, Patriot Blue, Platinum, Slate
AVAILABLE SEAT COLORS	Stone Beige, Black (Custom Colors Also Available)
AVAILABLE PREMIUM	Mushroom, Grey, Black, White (Custom Colors Also Available)





